

PRODUCT DESCRIPTION

CONTROL PLATFORM:

- Control platform with LCD, keyboard, mouse and single ports VGA KVM switch;
- 1U height, suitable for 19" standard cabinet installation and metal structure;
- 17" LED screen with high brightness, high clear and high resolution;
- Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees;
- Ultra thin keyboard with keypad;
- Mouse touch board with two function button;
- Front panel with lock to prevent damage by accident;
- Built-in power;
- Automatic power on/off. When pulling control platform out from cabinet, the power turns off automatically. When pushing it into the cabinet, the power turns on automatically;
- An easy to use OSD menu.

SWITCH:

- One control platform can control 1pcs computer by direct connection;
- Be compatible with USB/PS.2 standard interface;
- Support VGA, SVGA, XGA video input;
- Accord with DDC, DDC2, DDC2B standard and VESA standard;
- Support maximum resolution of 1920 x 1080;
- Support multiple operating systems: WIN95/98/98SE/ME/200X/XP/WIN7/ NT, UNIX, LINUX.



authorship, as well as modification of its content or context. All specifications are subject to change without notice. The pictures, drawings are merely illustrative.

More information: info@barpa.eu or in www.barpa.eu



• SPECIFICATIONS					
Computer Connection		1	8		
CPU Port Selection		Front panel buttons/OSD menu			
Console Connector	Keyboard	Disassembled standard 99-key keyboard			
	Mouse	Standard PS/2 touch pad; rear side with USB connector			
	Video	17 inch SXGA color TFT-LCD			
Cable Connectors	Keyboard	1 x PS/2 female (purple), 1 x USB female			
	Mouse	1 x PS/2 female (green), 1 x USB female			
	Video	1 x HDB-15 male (blue)			
LED's	Online	1 red LED's			
	Selected	1 green LED's			
LCD monitor	Monitor	17.0"SXGA Color TFT-LCD			
	Visible square	304.128(H) zx 228.096(V)mm			
	Resolution(max)	1920x1080 60HZ			
	Support Color	16.2 M / 262K colors			
	White Luminance	250 (center, Typ)@ 60 mA			
	Contrast	700:1 (Typ)			
	Back light	LED			
	Pixel Pitch	0.297(per one triad)x0.297			
	LCD MTBF	50,000hours			
	Input power	DC 12 V			
Keyboards	Keyboard	99keys			
	Compatible IBM/AT	Win95/98/98SE/ME/200/Win7 XP Vista WinNT Uni Linux			
	Port	Standard PS/2&USB			
	Using life	>1,000,000 times			
Mouse	X/Y resolution	1000dots/inch 40x40/mm)			
	Hardware connector	Standard PS/2&USB			
	Os support	Win95/98/98SE/ME/200X/Win7/XP/Vista/Win7/NT/UniX/Linux			
	Using life	>1,000,000 times			
Power	Power (AC)	~100V-240V			
	Using life	MTBF>60,000hours 25 °C			
Housing		Metal (black)			
Gross weight		21.35 KGS	22.74 KGS		
Dimensions		640x443	640x443x42mm		
Rack installation depth		800mm ~ 1200mm (adjustable)	600MM ~ 1200mm (adjustable)		
Operating/storage Temp (°C)		0~50/-20~60			

• ORDER INFORMATION	ON			
Code	Description	Unit Weight (kg)	Unit Dimmensions (mm)	Quantity (un)
82371117010	KVM Switch VGA 17" LCD 1 Port	21	805 x 695 x 190	1
82371117080	KVM Switch VGA 17" LCD 8 Ports	22,5	805 x 695 x 190	1
82372010000	IP Card for KVM Switch	0,07	110 x 68 x 22	1