

ORTAC METAL ACCESSORIES




METAL BLIND STOPS

BRASS

TECHNICAL DETAILS

Material : Brass with nickel plated
 Screw plug : NBR
 Connection thread : Metric (EN60423) / PG (DIN 40430)
 Protection class : IP68
 Temperature range : -40 °C +100 °C

Properties
 For unused threaded holes
 Assembling with screwdriver
 Machine and equipment manufacturing
 Electric motor manufacturing



PİRİNÇ KÖRTAPA

Hammaddesi : Pirinç, nikel kaplı
 Bağlantı dişi M : EN 60423
 Bağlantı dişi PG : DIN 40430
 Koruma sınıfı : IP68
 O-ring : Nitril kauçuk

METRIC/PG THREAD BLIND STOPS

AG Thread	Code	H mm	GL mm	D mm
M 12 x 1,5	OMBK 01	7,5	5	14
M 16 x 1,5	OMBK 02	8	5	18
M 20 x 1,5	OMBK 03	9,5	6,5	22
M 25 x 1,5	OMBK 04	11	7	28
M 32 x 1,5	OMBK 05	12	8	35
M 40 x 1,5	OMBK 06	13	8,5	44
M 50 x 1,5	OMBK 07	15	9	54
M 63 x 1,5	OMBK 08	16	10	67
PG 7	OPBK 01	8	5	14
PG 9	OPBK 02	9	6	17
PG 11	OPBK 03	9	6	20
PG 13,5	OPBK 04	9,5	6,5	22
PG 16	OPBK 05	9,5	6,5	24
PG 21	OPBK 06	11	7	30
PG 29	OPBK 07	12	8	39
PG 36	OPBK 08	15	9	50
PG 42	OPBK 09	16	10	57
PG 48	OPBK 10	16	10	64

PRODUCT RANGE OVERVIEW

IP 68