


# **Technical specifications**

BOX-ACC-FF-SQ (Fixed frame floorbox square)



## Category:

BOX-ACC-FF-SQ

#### Product features

Material: PA6 reinforced fibre glass, flame retardant Colour: RAL5010 (blue)

### Additional productinformation:

For raising the maximum screed height

Each frame increases the maximum screed height by 30 mm

The frames click together

Rotate the frames a quarter turn relatively to each other to ensure they are firmly clicked together


The bottom frame clicks onto the metal cover of the floor box

The adjustment frame (green) is always fitted onto the top-most fixed (blue) frame



Execution:	Polyamide reinforced fibre glass, blue										
Product	Number	Height	Width	Length	Dim A	Fmax	Unit	Packaging			
		(mm)	(mm)	(mm)	(mm)	(kN)		(unit)			
FS-FF-SQ-34-260-PAG5010	15643	34	315	315			ST	1			

Mounting instructions:



# Additional mounting information:

	1x FS-FF-SQ-34-260			SQ-34-260	3x FS-FF-SQ-34-260		
	Min H (mm)	Max H (mm)	Min H (mm)	Max H (mm)	Min H (mm)	Max H (mm)	
BOX28	67	97	97	127	127	157	
BOX38	77	107	107	137	137	167	
BOX48	87	117	117	147	147	177	

Peripheral information:

EC conformity:

EC directive 2006/95/EC (Low voltage) as modified by directive 93/68/EEC (CE marking)