

Polyester braided sleeve

TECHNICAL SPECIFICATIONS	TYPICAL VALUES	TESTING METHOD
tensile strenght	4.80 kg/mm ²	ISO 37
elongation at break	28–35 %	ISO 37
specific weight	1.38 g/cm ³	ISO R1183
water absorption	0.5% max	ASTM D570
self-extinguishing rating	HB	UL 94

Applications

- Protection and assembly of electrical, electronic and telephone cables
- Civil, industrial, and automotive wiring

Advantages

- Good mechanical resistance
- High tensile strength
- Removable
- Good resistance to chemicals
- Good resistance to UV rays

Features

- Tubular braided sleeve
- Premium quality single thread polyester
- Self-extinguishing HB according to UL 94
- Operating temperature: -50 / 170 °C
- Melting pot: 260 °C
- Non-toxic
- Halogen-free



COBRABOX

Polyester braided sleeve
in dispenser

- Handy package
- Colour grey

Selection table

item	rated diameter (mm)	diameter of ligation (mm)		Spool length (m)
		min	max	
COBRABOX 03	3	2	8	25
COBRABOX 04	4	3	9	25
COBRABOX 05	5	4	11	25
COBRABOX 06	6	5	15	25
COBRABOX 08	8	6	18	20
COBRABOX 10	10	8	21	20
COBRABOX 12	12	10	20	10
COBRABOX 15	15	12	29	10
COBRABOX 20	20	15	33	10
COBRABOX 25	25	20	45	10
COBRABOX 30	30	25	48	5
COBRABOX 40	40	35	60	3
COBRABOX 50	50	45	75	3